

CSS

“Cascading Style Sheets”

Comments:

```
/* CSS comments (ignored by browser) */
```

```
<!-- HTML comment (ignored by browser) -->
```

CSS Rules

CSS rules determine the appearance, the “style” of what is rendered in the browser window.

They have **five parts**:

- selector
- declaration block
- declaration
- property
- value

The **selector** “selects” the elements on an HTML page that are affected by the rule.

```
/* CSS rule */
```

```
p { }
```



selector

```
<!-- HTML markup -->
```

```
<p>
```

```
This is a sentence.<br>
```

```
</p>
```

The **declaration block** is everything inside the curly braces. “{ }”

```
/* CSS rule */  
p { }
```




declaration block

```
<!-- HTML markup -->
```

```
<p>  
This is a sentence.<br>  
</p>
```

The **declaration** tells the browser how to render the selected element.


```
/* CSS rule */  
p { color: red; }
```




```
<!-- HTML markup -->
```

```
<p>  
This is a sentence.<br>  
</p>
```

The **property** names what aspect of the element is to be styled.
It is followed by a colon.

-For example the color.

```
/* CSS rule */  
p { color: red; }
```




```
<!-- HTML markup -->
```

```
<p>  
This is a sentence.<br>  
</p>
```

The **value** is the particular style you want to assign to the property.
It ends with a semicolon.

```
/* CSS rule */  
p { color: red; }
```



```
<!-- HTML markup -->
```

```
<p>  
This is a sentence.<br>  
</p>
```

The **lots of properties** that can be defined for the various selectors.

```
p { color: green; }
```

```
p { font-size: 32px; }
```

```
p { text-align: right; }
```

```
p { width: 900px; }
```

```
p { border: 1px; }
```

```
p { border-style: dashed; }
```

```
p { color: green; }  
p { font-size: 32px; }
```

--The CSS
rules can be
listed on
separate lines.

```
p {  
  text-align: right;  
  width: 900px;  
  border: 1px;  
  border-style: dashed;  
}
```

--But usually
they are
listed in a
block.

2 Kinds of Custom CSS Selectors:

- **id** (Unique, Used once on a page.)
- **class** (can be used multiple times on a page.)

2 Kinds of Custom CSS Selectors:

id

```
#TopOfPage {  
    text-align: center;  
    font-style: italic;  
}
```

```
<div id="TopOfPage">  
    Styled content  
</div>
```

2 Kinds of Custom CSS Selectors:

class

```
.italicText {  
    font-style: italic;  
}
```

```
<p class="italicText">  
    Styled content  
</div>
```

2 places to have your CSS:

1. Embedded:

(Enclosed in the “style” tag within the HTML document):

```
<style>
  .italicText {
    font-style: italic;
  }
</style>
```

2. External:

(Referenced with a link in the HEAD):

```
<link rel="stylesheet" href="styles.css">
```